

## PROCOOL PC2 V/G COOLING SYSTEM



### Specifications

- Factory set at 50 psi adjustable to 80 psi
  - 3 gallon reservoir

- 115 or 230 VAC / 1 ph-50/60Hz
  - 5.6 / 2.8 amp:60 Hz
  - 12,000 BTU
- Dimensions: 18"L x 14"W x 9"H
  - Net weight: 37 lbs / 17 kg
- Foam packed for UPS shipment

**PCIIG: Rotary GEAR Pump**

- 1.8 gpm at 50 psi
- Built in by-pass to tank
- Rebuildable Pump (Repair Kit Product No. P3001)

**PCIIV: Rotary VANE Pump**

1.7 gpm at 50 psi

**System Features**

- Plastic water tank eliminates coolant contamination due to electrolysis or chemical reactions.
  - All units are plumbed with copper tubing and reinforced hose.
- New extended life pump features a direct drive power system reducing maintenance and vibration.
- No external plumbing is required because of closed loop water system.
  - Self priming pump
  - Easy change pump
- Strong rigid construction designed to support power unit.
  - Compact design

<b>Equipment</b>	<b>UPTO</b>
M.I.G. guns	500 amps
T.I.G. torches	500 amps
RESISTANCE Welders	60 KVA

**GALLERY IMAGES**

